



# BD177

The BD177 features an aggressive, open shoulder tread design which improves self-cleaning to deliver exceptional traction in mud and snow. Its staggered tread block pattern distributes load evenly to resist irregular wear. The BD177 is engineered with a deep 25/32\*\* tread depth to provide a long tread life. \*Exception: 10R22.5.

#### APPLICATIONS

- Refuse Trucks
- Dump Trucks
- Regional Trucks
- Ready Mix Trucks

#### TIRE FEATURES

- Open shoulder design delivers superior traction.
- Staggered tread blocks resist irregular wear.
- Deep tread depth for excellent tread life.

La BD177 cuenta con un diseño agresivo de hombro abierto que mejora la auto-limpieza de la llanta para proporcionar una tracción excepcional en el lodo y la nieve. Su patrón de piso en bloques distribuye la carga por igual, resistiendo el desgaste irregular. La BD177 está diseñado con una profundidad de piso de 25/32vos\*\* de pulgada que otorga una vida útil más larga al piso de la llanta. \*Excepción: 10R22.5.

#### APLICACIONES

- Camiones de basura
- Camiones de volcar
- Camiones regionales
- Camiones de premezclado

#### CARACTERÍSTICAS

- Tiene un diseño abierto de hombro para una tracción excelente.
- Su patrón de piso en bloques resiste el desgaste irregular.
- Su diseño profundo del piso de la llanta le da una vida útil más larga.



Size	Ply	T.D.		Load Index		S.R.	O.D.	S.W.	R.W.	Load Carrying Capacity		A.P.
		32nds		Single	Dual					in.	in.	
10R22.5	14	23		141	139	M	40.6	10.0	7.50	5,675	5,355	115
11R22.5	14	25		144	142	L	41.5	11.0	8.25	6,175	5,840	105
11R22.5	16	25		146	143	L	41.5	11.0	8.25	6,610	6,005	120
255/70R22.5	16	24		140	137	L	36.9	10.0	7.50	5,510	5,070	120
11R24.5	14	25		146	143	L	43.5	11.0	8.25	6,610	6,005	105
11R24.5	16	25		149	146	L	43.5	11.0	8.25	7,160	6,610	120