



# BT166 FST

The Blacklion BT166 FST is designed specifically for trailer applications. The BT166 FST is engineered with an advanced rubber compound which delivers excellent tread wear and fuel saving performance. The BT166 FST tread design resists irregular tread wear and minimizes skid wear. Its wide center groove delivers superior water evacuation.

#### APPLICATIONS

- Long-Distance Trailers (Tandem)

#### TIRE FEATURES

- SmartWay verified tires can improve fuel efficiency by 3 percent or more.
- Shallow tread reduces irregular wear.
- Optimized casing reduces rolling resistance.
- Solid shoulder ribs minimize skid wear.

La Blacklion BT166 FST está específicamente hecha para aplicaciones de remolques. La BT166 FST está diseñada con un compuesto de avanzada de caucho que proporciona un coeficiente de desgaste y ahorro de combustible supremo. El diseño del piso de la llanta de la BT166 FST resiste el desgaste irregular y minimiza el desgaste causado por el derrapado. Su canal ancho central permite una evacuación superior de agua.

#### APLICACIONES

- Remolques de larga distancia (Tándem)

#### CARACTERÍSTICAS

- Su piso poco profundo reduce el desgaste irregular.
- La carcasa optimizada reduce la resistencia al rodamiento.
- Las costillas solidas del hombro minimizan el desgaste por derrape.



**SMARTWAY VERIFIED TIRE**  
LLANTAS CON VERIFICACIÓN SMARTWAY

Size	Ply	T.D.	Load Index		S.R.	O.D.	S.W.	R.W.	Load Carrying Capacity		A.P.
			Single	Dual					Single, lbs.	Dual, lbs.	
11R22.5	14	32nds	144	142	L	41.5	11.0	8.25	6,175	5,840	105
*255/70R22.5	16	12	140	137	M	36.6	10.0	7.50	5,510	5,070	120
295/75R22.5	14	12	144	141	L	39.9	11.7	8.25	6,175	5,675	110
11R24.5	14	12	146	143	L	43.5	11.0	8.25	6,610	6,005	105
285/75R24.5	14	12	144	141	L	41.3	11.1	8.25	6,175	5,675	110

\* Tire size is not SmartWay® Verified \*Este tamaño de llanta no tiene verificación SmartWay®